

Safety Data Sheet dated 16/1/2023, version 2.1 This version cancels and substitutes any previous version

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification: Trade name: CLEANSI

1.2. Relevant identified uses of the substance or mixture and uses advised against Recommended use:
Purifying treatment for Surfaces 80% alcohol Based
1.3. Details of the supplier of the safety data sheet

Company: ERRECOM SPA Via Industriale, 14 Corzano (BS) Italy Tel. +39 030/9719096 Competent person responsible for the safety data sheet: lab@errecom.it 1.4. Emergency telephone number

+39 02-6610-1029 Poison Control Center Niguarda Ca' Granda - Milano - ITALY

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture EC regulation criteria 1272/2008 (CLP)

Danger, Aerosols 1, Extremely flammable aerosol. Pressurized container: may burst if heated.

Warning, Eye Irrit. 2, Causes serious eye irritation.



Warning, STOT SE 3, May cause drowsiness or dizziness.

Adverse physicochemical, human health and environmental effects:

No other hazards 2.2. Label elements Hazard pictograms:



Danger

Hazard statements:

H222, H229 Extremely flammable aerosol. Pressurized container: may burst if heated. H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

CLEANSI/2.1 Page n. 1 of 10



P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. P501 Dispose of contents/container in accordance with applicable regulations. Special Provisions:

None

Contains

propan-2-ol

Special provisions according to Annex XVII of REACH and subsequent amendments: None

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

- N.A.
- 3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb	er	Classification
>= 70% - < 80%	propan-2-ol	Index number: CAS: EC: REACH No.:	603-117-00-0 67-63-0 200-661-7 01-21194575 58-25-XXXX	 2.6/2 Flam. Liq. 2 H225 3.3/2 Eye Irrit. 2 H319 3.8/3 STOT SE 3 H336
>= 15% - < 20%	propane	Index number: CAS: EC: REACH No.:	601-003-00-5 74-98-6 200-827-9 01-21194869 44-21-XXXX	 2.2/1A Flam. Gas 1A H220 2.5 Press. Gas H280
>= 7% - < 10%	butane	Index number: CAS: EC: REACH No.:	601-004-00-0 106-97-8 203-448-7 01-21194746 91-32-XXXX	 2.2/1A Flam. Gas 1A H220 2.5 Press. Gas H280
>= 2.5% - < 5%	isobutane	Index number: CAS: EC: REACH No.:	601-004-00-0 75-28-5 200-857-2 01-21194853 95-27-XXXX	 2.2/1A Flam. Gas 1A H220 2.5 Press. Gas H280

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

After contact with skin, wash immediately with soap and plenty of water. Wash contaminated clothing before using them.

In case of eyes contact:

CLEANSI/2.1 Page n. 2 of 10



After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

- 4.2. Most important symptoms and effects, both acute and delayed No information available.
- 4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Treatment:

- Nono
- None

SECTION 5: Firefighting measures

- 5.1. Extinguishing media
 - Suitable extinguishing media:
 - Water spray jet, alcohol resistant foam, extinguishing powder, carbon dioxide. Extinguishing media which must not be used for safety reasons: None in particular.
- 5.2. Special hazards arising from the substance or mixture Do not inhale explosion and combustion gases. Burning produces heavy smoke.
- 5.3. Advice for firefighters
 - Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures
 - For non emergency personnel:
 - Wear personal protection equipment.
 - Remove all sources of ignition.
 - Remove persons to safety.
 - See protective measures under point 7 and 8.
 - For emergency responders:

Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

- Suitable material for taking up: absorbing material, organic, sand
- 6.3. Methods and material for containment and cleaning up
 - Wash with plenty of water.
- 6.4. Reference to other sections See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

CLEANSI/2.1 Page n. 3 of 10



Don't use empty container before they have been cleaned. Before making transfer operations, assure that there aren't any incompatible material residuals in the containers. Advice on general occupational hygiene: Contamined clothing should be changed before entering eating areas. Do not eat or drink while working. See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight. Keep away from food, drink and feed. Incompatible materials: See subsection 10.5

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s) Information not available.

SECTION 8: Exposure controls/personal protection

- 8.1. Control parameters
 - propan-2-ol CAS: 67-63-0

ACGIH - TWA(8h): 200 ppm - STEL: 400 ppm - Notes: A4, BEI - Eye and URT irr, CNS impair

MAK - TWA(8h): 500 mg/m3, 200 ppm - STEL(15min): 1000 mg/m3, 400 ppm VLA - TWA(8h): 500 mg/m3, 200 ppm - STEL(15min): 1000 mg/m3, 400 ppm VLEP - STEL(15min): 980 mg/m3, 400 ppm

WEL - TWA(8h): 999 mg/m3, 400 ppm - STEL(15min): 1250 mg/m3, 500 ppm TLV - TWA(8h): 980 mg/m3, 400 ppm - STEL(15min): 1225 mg/m3, 500 ppm NDS - TWA(8h): 900 mg/m3 - STEL(15min): 1200 mg/m3

NPHV - TWA(8h): 500 mg/m3, 200 ppm - STEL(15min): 1000 mg/m3 MV - TWA(8h): 500 mg/m3, 200 ppm - STEL(15min): 2000 mg/m3, 800 ppm GVI - TWA(8h): 999 mg/m3, 400 ppm - STEL(15min): 1250 mg/m3, 500 ppm TLV (CZ) - TWA(8h): 500 mg/m3, 200 ppm - STEL(15min): 1000 mg/m3, 400 ppm TLV (EST) - TWA(8h): 350 mg/m3, 150 ppm - STEL(15min): 600 mg/m3, 250 ppm propane - CAS: 74-98-6

ACGIH - Notes: (D, EX) - Asphyxia

butane - CAS: 106-97-8

ACGIH - STEL: 1000 ppm - Notes: (EX) - CNS impair

isobutane - CAS: 75-28-5

ACGIH - STEL: 1000 ppm - Notes: (EX) - CNS impair

- **DNEL Exposure Limit Values**
 - propan-2-ol CAS: 67-63-0

Consumer: 26 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

Worker Industry: 500 mg/m³ - Consumer: 89 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 888 mg/kg - Consumer: 319 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

propan-2-ol - CAS: 67-63-0

Target: Fresh Water - Value: 140.9 mg/L

Target: Marine water - Value: 140.9 mg/L

Target: Freshwater sediments - Value: 552 mg/kg

Target: Aquatic, periodic release - Value: 140.9 mg/L



Target: Microorganisms in sewage treatments - Value: 2251 mg/L Target: Marine water sediments - Value: 552 mg/kg Target: Soil (agricultural) - Value: 28 mg/kg 8.2. Exposure controls Eye protection: Tightly fitting safety goggles. Protection for skin: Not needed for normal use. Protection for hands: Suitable material: PVC (polyvinyl chloride). NR (natural rubber, natural latex). CR (polychloroprene, chloroprene rubber). work gloves resistant to penetration (ref. standard EN 374). Material thickness: minimum 0.12 mm. Break through time : > 480 min Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). One-time gloves. Respiratory protection: Use adequate protective respiratory equipment. Mask with filter "A", brown colour Thermal Hazards: None Environmental exposure controls: None Appropriate engineering controls: None

SECTION 9: Physical and chemical properties

Properties	Value	Method:	Notes:
Physical state:	Liquid		
Colour:	Colourless		
Odour:	characteristic		
Melting point/freezing	N.A.		
point:			
Boiling point or initial	N.A.		
boiling point and boiling			
range:			
Flammability:	N.A.		
Lower and upper explosion	N.A.		
limit:			
Flash point:	< 0 ° C		
Auto-ignition temperature:	N.A.		
Decomposition	N.A.		
temperature:			
pH:	7		
Kinematic viscosity:	N.A.		
Solubility in water:	partial		
Solubility in oil:	total		
Partition coefficient	N.A.		
n-octanol/water (log value):			

CLEANSI/2.1 Page n. 5 of 10



Vapour pressure:	N.A.		
Density and/or relative	0.8 g/mL		
density:	(+20°C/+68°F		
)		
Relative vapour density:	N.A.		
Particle characteristics:			
Particle size:	N.A.		

9.2. Other information

No other relevant information

SECTION 10: Stability and reactivity

- 10.1. Reactivity
 - Stable under normal conditions
- 10.2. Chemical stability
 - Stable under normal conditions
- 10.3. Possibility of hazardous reactions

It can generate flammable gases in contact with elementary metals (alkalis and alkaline earth), nitrides, strong reducing agents.

It can ignite in contact with oxidizing mineral acids, elementary metals (alkalis and alkaline earths), nitrides, peroxides and organic hydroperoxides, oxidizing agents and reducing agents.

10.4. Conditions to avoid

Avoid overheating, electrostatic discharge and all sources of ignition.

- 10.5. Incompatible materials
- Strong oxidizing agents.
- 10.6. Hazardous decomposition products When heated or in the event of fire may release gases and vapors potentially dangerous to health.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008Toxicological information of the product:a) acute toxicity

- Not classified
- Based on available data, the classification criteria are not met
- b) skin corrosion/irritation
 - Not classified
 - Based on available data, the classification criteria are not met
- c) serious eye damage/irritation
 - The product is classified: Eye Irrit. 2 H319
- d) respiratory or skin sensitisation
 - Not classified
- Based on available data, the classification criteria are not met
- e) germ cell mutagenicity
 - Not classified
- Based on available data, the classification criteria are not met f) carcinogenicity
 - Not classified
- Based on available data, the classification criteria are not met g) reproductive toxicity
 - Not classified
 - Based on available data, the classification criteria are not met

CLEANSI/2.1 Page n. 6 of 10



h) STOT-single exposure The product is classified: STOT SE 3 H336 i) STOT-repeated exposure Not classified Based on available data, the classification criteria are not met i) aspiration hazard Not classified Based on available data, the classification criteria are not met Toxicological information of the main substances found in the product: propan-2-ol - CAS: 67-63-0 a) acute toxicity: Test: LD50 - Route: Oral - Species: Rat 4710 mg/kg Test: LD50 - Route: Skin - Species: Rat 12800 mg/kg Test: LC50 - Route: Inhalation - Species: Rat 72.6 mg/L - Duration: 4h Test: LD50 - Route: Skin - Species: Rabbit 6290 mg/kg 11.2. Information on other hazards Endocrine disrupting properties: No endocrine disruptor substances present in concentration >= 0.1%

SECTION 12: Ecological information

12.1. Toxicity Adopt good working practices, so that the product is not released into the environment. Not classified for environmental hazards Based on available data, the classification criteria are not met propan-2-ol a) Aquatic acute toxicity: Endpoint: EC0 - Species: Fish 10000 mg/L - Duration h: 48 - Notes: Pimephales promelas Endpoint: LC50 - Species: Fish > 1400 mg/L - Duration h: 96 - Notes: Lepomis macrochirus Endpoint: LC50 - Species: Fish 6550 mg/L - Duration h: 96 - Notes: Pimephales promelas 12.2. Persistence and degradability propan-2-ol - CAS: 67-63-0 Biodegradability: Readily biodegradable 12.3. Bioaccumulative potential propan-2-ol - CAS: 67-63-0 Bioaccumulation: Not bioaccumulative - Test: Kow - Partition coefficient 0.05 12.4. Mobility in soil NΑ 12.5. Results of PBT and vPvB assessment vPvB Substances: None - PBT Substances: None 12.6. Endocrine disrupting properties No endocrine disruptor substances present in concentration >= 0.1%12.7. Other adverse effects None

SECTION 13: Disposal considerations

13.1. Waste treatment methods Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information

CLEANSI/2.1 Page n. 7 of 10



14.1. UN number or ID number	
ADR-UN number:	1950
IATA-Un number:	1950
IMDG-Un number:	1950
14.2. UN proper shipping name	
ADR-Shipping Name:	AEROSOLS, flammable
IATA-Shipping Name:	Aerosols, flammable
IMDG-Shipping Name:	AEROSOLS
14.3. Transport hazard class(es)	
ADR-Class:	2
ADR-Label:	2.1
IATA-Class:	2.1
IMDG-Class:	2.1
14.4. Packing group	
14.5. Environmental hazards	
Marine pollutant:	No
IMDG-EMS:	F-D, S-U
14.6. Special precautions for user	
ADR-Transport category (Tunr	nel restriction code): D
IATA-Passenger Aircraft:	Y203
IATA-Cargo Aircraft:	Y203
IMDG-Shipping Name:	AEROSOLS
14.7. Maritime transport in bulk accor	ding to IMO instruments
N.A.	

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Dir. 98/24/EC (Risks related to chemical agents at work) Dir. 2000/39/EC (Occupational exposure limit values) Regulation (EC) n. 1907/2006 (REACH) Regulation (EC) n. 1272/2008 (CLP) Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013 Regulation (EU) n. 2020/878 Regulation (EU) n. 286/2011 (ATP 2 CLP) Regulation (EU) n. 618/2012 (ATP 3 CLP) Regulation (EU) n. 487/2013 (ATP 4 CLP) Regulation (EU) n. 944/2013 (ATP 5 CLP) Regulation (EU) n. 605/2014 (ATP 6 CLP) Regulation (EU) n. 2015/1221 (ATP 7 CLP) Regulation (EU) n. 2016/918 (ATP 8 CLP) Regulation (EU) n. 2016/1179 (ATP 9 CLP) Regulation (EU) n. 2017/776 (ATP 10 CLP) Regulation (EU) n. 2018/669 (ATP 11 CLP) Regulation (EU) n. 2018/1480 (ATP 13 CLP) Regulation (EU) n. 2019/521 (ATP 12 CLP) Regulation (EU) n. 2020/217 (ATP 14 CLP) Regulation (EU) n. 2020/1182 (ATP 15 CLP) Regulation (EU) n. 2021/643 (ATP 16 CLP) Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications: Restrictions related to the product: **Restriction 3** Restriction 40

Restrictions related to the substances contained:

CLEANSI/2.1 Page n. 8 of 10



Restriction 75

Where applicable, refer to the following regulatory provisions : Directive 2012/18/EU (Seveso III) Regulation (EC) nr 648/2004 (detergents). Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III): Seveso III category according to Annex 1, part 1 Product belongs to category: P3a

15.2. Chemical safety assessment No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Full text of phrases referred to in Section 3:

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

Hazard class and hazard category	Code	Description
Flam. Gas 1A	2.2/1A	Flammable gas, Category 1A
Aerosols 1	2.3/1	Aerosol, Category 1
Press. Gas	2.5	Gases under pressure
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure,
		Category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Aerosols 1, H222, H229	On basis of test data
Eye Irrit. 2, H319	Calculation method
STOT SE 3, H336	Calculation method

This document was prepared by a competent person who has received appropriate training. Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

CLEANSI/2.1 Page n. 9 of 10

